




Globe Valves


Class 800 • Standard Port – Bolted Bonnet – Threaded and Socketweld Ends

Dimensions	Thrd	Thrd x SWE	SWE	Size (in.)							
				3/8	1/2	3/4	1	1 1/4	1 1/2	2	
Standard Port	4221	4201	4211								
End to End		A		3.19	3.19	3.46	4.33	6.06	6.06	6.73	
Handwheel		B		3.62	3.62	3.62	4.02	5.12	5.91	6.89	
Center to Top		C (Closed)		5.71	6.10	6.26	7.04	8.98	9.21	10.12	
Port Diameter		D		.28	.39	.49	.69	.94	1.14	1.30	
Weight		Lbs.		4.19	4.19	5.73	7.94	14.77	14.77	26.46	




Class 1500 • Standard Port – Bolted Bonnet – Threaded and Socketweld Ends

Dimensions	Thrd	Thrd x SWE	SWE	Size (in.)							
				3/8	1/2	3/4	1	1 1/4	1 1/2	2	
Standard Port	6221	6201	6211								
End to End		A		3.19	3.46	4.33	5.04	5.04	5.51	5.94	
Handwheel		B		3.62	3.62	4.02	5.12	5.12	5.91	6.89	
Center to Top		C (Closed)		5.59	5.79	6.69	7.76	8.46	9.37	10.98	
Port Diameter		D		.28	.37	.50	.71	.94	1.20	1.44	
Weight		Lbs.		4.19	5.73	7.94	10.58	16.53	23.59	35.27	




Class 800 • Standard Port – Welded Bonnet – Threaded and Socketweld Ends

Dimensions	Thrd	Thrd x SWE	SWE	Size (in.)							
				3/8	1/2	3/4	1	1 1/4	1 1/2	2	
Standard Port	4223	4203	4213								
End to End		A		3.19	3.19	3.46	4.33	6.06	6.06	6.73	
Handwheel		B		3.62	3.62	3.62	4.02	5.12	5.91	6.89	
Center to Top		C (Closed)		5.71	6.10	6.26	7.05	8.97	9.21	10.12	
Port Diameter		D		.28	.39	.49	.69	.94	1.14	1.30	
Weight		Lbs.		3.97	3.97	4.85	6.61	14.77	14.77	26.46	



Class 1500 • Standard Port – Welded Bonnet – Threaded and Socketweld Ends


Dimensions	Thrd	Thrd x SWE	SWE	Size (in.)							
				—	1/2	3/4	1	1 1/4	1 1/2	2	
Standard Port	6223	6203	6213								
End to End		A		—	3.46	4.31	5.06	6.06	6.06	8.31	
Handwheel		B		—	3.62	4.02	5.12	5.91	5.91	6.89	
Center to Top		C (Closed)		—	6.26	7.05	8.46	8.98	9.21	12.40	
Port Diameter		D		—	.39	.50	.69	.94	1.13	1.30	
Weight		Lbs.		—	5.95	7.94	10.58	14.77	19.84	28.66	



Globe Valves


Class 1500 • Full Port—Y Pattern—Welded Bonnet—Threaded and Socketweld Ends

Dimensions	Thrd	SWE	Size (in.)					
Full Port	6273Y	6263Y	1/2	3/4	1	1 1/4	1 1/2	2
End to End	A		4.37	5.98	7.52	7.52	8.50	8.50
Handwheel	B		4.02	5.12	6.89	6.89	6.89	6.89
Center to Top	C (Closed)		7.87	9.45	11.81	11.81	13.78	13.78
Port Diameter	D		.43	.57	.75	.91	1.26	1.46
Weight	Lbs.		8.37	14.33	33.07	33.07	39.68	39.68



Class 2500 • Full Port—Y Pattern—Welded Bonnet—Threaded and Socketweld Ends

Dimensions	Thrd	SWE	Size (in.)					
Full Port	7273Y	7263Y	1/2	3/4	1	1 1/4	1 1/2	2
End to End	A		5.98	7.52	7.52	8.50	8.50	8.5
Handwheel	B		5.12	6.89	6.89	7.48	7.48	7.48
Center to Top	C (Closed)		9.45	11.81	11.81	13.78	13.78	13.78
Port Diameter	D		.43	.57	.75	.91	1.26	1.46
Weight	Lbs.		8.37	14.33	33.07	33.07	39.68	39.68



For years Industry professionals have specified DSI® valve products for their most demanding projects, and consistently Zy-Tech Global Industries delivers the highest performance fluid control products available anywhere.


Ask your DSI® representative about our other fine flow control products.



Globe Valves


Class 150 • Standard Port – Bolted Bonnet – Flanged Ends

Dimensions	Flanged End	Size (in.)				
		1/2	3/4	1	1 1/2	2
Standard Port	1231	1/2	3/4	1	1 1/2	2
Face to Face	A	4.25	4.61	5.00	6.50	8.00
Handwheel	B	3.62	3.62	4.02	5.91	6.89
Center to Top	C (Closed)	6.97	7.44	7.60	9.45	10.12
Port Diameter	D	.39	.49	.67	.98	1.30
Weight	Lbs.	6.61	10.58	13.23	22.05	33.07




Class 300 • Standard Port – Bolted Bonnet – Flanged Ends

Dimensions	Flanged End	Size (in.)				
		1/2	3/4	1	1 1/2	2
Standard Port	2231	1/2	3/4	1	1 1/2	2
Face to Face	A	5.98	7.00	7.99	9.02	10.51
Handwheel	B	3.62	3.62	4.02	5.91	6.89
Center to Top	C (Closed)	6.97	7.44	7.60	9.45	10.12
Port Diameter	D	.39	.49	.67	.98	1.30
Weight	Lbs.	9.92	12.13	17.64	26.46	37.48



Class 600 • Standard Port – Bolted Bonnet – Flanged Ends

Dimensions	Flanged End	Size (in.)				
		1/2	3/4	1	1 1/2	2
Standard Port	3231	1/2	3/4	1	1 1/2	2
Face to Face	A	6.50	7.50	8.50	9.50	11.50
Handwheel	B	3.62	3.62	4.02	5.91	6.89
Center to Top	C (Closed)	6.97	7.44	7.60	9.49	10.12
Port Diameter	D	.39	.49	.67	.98	1.30
Weight	Lbs.	9.92	13.89	18.52	38.36	49.96



Class 1500 • Full Port – RTJ – Bolted Bonnet – Flanged Ends

Dimensions	Flanged End	Size (in.)				
		1/2	3/4	1	1 1/2	2
Full Port	6287	1/2	3/4	1	1 1/2	2
Face to Face	A	8.50	9.02	10.00	12.01	14.49
Handwheel	B	5.12	5.91	5.91	6.89	6.89
Center to Top	C (Closed)	11.10	12.28	12.76	13.90	14.29
Port Diameter	D	.43	.57	.75	1.24	1.48
Weight	Lbs.	28.66	35.27	47.40	83.77	132.28

